



ROF -TLS series

Tunable laser light source

Product description

The ROF -TLS tunable laser light source utilizes high performance DFB laser, and a tunable laser light source with a fixed wavelength interval (50 GHz) and its tunable range is over 40nm. The product's wavelength internal locking function ensures that the output wavelength or frequency is in DWDM Channel on the ITU grid. It has high output power (10mW), narrow linewidth、high wavelength accuracy、good power stability and so on. It can achieve remote control of the instrument, being mainly used in WDM device testing、optical fiber sensing、PMD and PDL measurement and optical coherence tomography (OCT) and other fields.

Features

- Wavelength tuning range
- Output power 10mw
- Narrow line width
- Internal locked of wavelength
- Remote control is available

Applications

- WDM device testing
- Optical fiber sensing
- PMD and PDL testing
- OCT

Parameter parameters


Parameter	Symbol	Min	Typ	Max	Unit
Wavelength	C-band	I	1524	1565	nm
	L-band	I	1560	1620	
Wavelength tuning range		40			nm
Channel spacing			50		GHz
Wavelength conversion speed			2		s
Wavelength accuracy		-1.5		1.5	GHz
Output optical power		Po	10		dBm
3dB spectral width		D1*	3	10	MHz
SMSR		SMSR	40	50	dB

Polarization extinction ratio	PEX	20			dB
Relative noise intensity	RIN		-145	-135	dB/Hz
Power stability **	PSS			±0.005	dB/5min
	PLS			±0.01	dB/8h
Output isolation	ISO	30	35		dB
Specification				Module	
Dimensions L x W x H			320×220×90 mm		
Power supply			AC 220V ± 10% 30W		
Output optical fiber			PMF		
Optical connector			FC/PC FC/APC or user specified		

Limit conditions

Parameter	Symbol	Unit	Min	Max
Operating temperature	Top	°C	-5	55
Storage temperature	Tst	°C	-40	85
Humidity	RH	%	5	90

Typical spectrum



Ordering information

ROF	TLS	X	10	P	XX
-----	-----	---	----	---	----

	Tunable laser light source	C---1525~1565nm L---1560~1620nm	Power : 10---10mW	Pigtail fiber : P--- PMF	Optical connector : FP --- FC/PC FA--- FC/APC SP--user specified
--	----------------------------	------------------------------------	----------------------	-----------------------------	---

*please contact our seller if you have special requirement